

IN 系列接线端子 IN SERIES TERMINAL BLOCKS



*IN系列可快捷方便的卡在35mm的卡轨上。并且拆卸非常容易。
*绝缘电流20A-400A。
*绝缘电压600V。
*无需分隔片。

* Type "IN" can be fit on and removed from 35mm wide Din rails quickly and easily.
* Insulation Current Capacity: 20A-400A.
* Insulation Voltage: 600V.
* Space slice no need.

TYPE:IN12BK-C	Ratings
Dimensions(mm) 	定格绝缘电压 Rated Insulation Voltage
	600V
定格绝缘电流 Rated Insulation Current	20A
	耐电压 Support Voltage
绝缘抵抗 Insulation Resistance	100MΩMIN
适合电线 Applicable Wire**	2mm2Max
极数 Number of poles	2Poles

TYPE:IN20BK-C	Ratings
Dimensions(mm) 	定格绝缘电压 Rated Insulation Voltage
	600V
定格绝缘电流 Rated Insulation Current	30A
	耐电压 Support Voltage
绝缘抵抗 Insulation Resistance	100MΩMIN
适合电线 Applicable Wire**	3.5mm2Max
极数 Number of poles	3Poles

TYPE:IN411SB-C	Ratings
Dimensions(mm) 	定格绝缘电压 Rated Insulation Voltage
	600V
定格绝缘电流 Rated Insulation Current	60A
	耐电压 Support Voltage
绝缘抵抗 Insulation Resistance	100MΩMIN
适合电线 Applicable Wire**	14mm2Max
极数 Number of poles	1Poles

TYPE:IN100K-C	Ratings
Dimensions(mm) 	定格绝缘电压 Rated Insulation Voltage
	600V
定格绝缘电流 Rated Insulation Current	130A
	耐电压 Support Voltage
绝缘抵抗 Insulation Resistance	100MΩMIN
适合电线 Applicable Wire**	38mm2Max
极数 Number of poles	1Poles

TYPE:IN400K-C	Ratings
Dimensions(mm) 	定格绝缘电压 Rated Insulation Voltage
	600V
定格绝缘电流 Rated Insulation Current	370A
	耐电压 Support Voltage
绝缘抵抗 Insulation Resistance	100MΩMIN
适合电线 Applicable Wire**	200mm2Max
极数 Number of poles	1Poles

TYPE:IN13SBK-C	Ratings
Dimensions(mm) 	定格绝缘电压 Rated Insulation Voltage
	600V
定格绝缘电流 Rated Insulation Current	20A
	耐电压 Support Voltage
绝缘抵抗 Insulation Resistance	100MΩMIN
适合电线 Applicable Wire**	2mm2Max
极数 Number of poles	3Poles

TYPE:IN30BK-C	Ratings
Dimensions(mm) 	定格绝缘电压 Rated Insulation Voltage
	600V
定格绝缘电流 Rated Insulation Current	50A
	耐电压 Support Voltage
绝缘抵抗 Insulation Resistance	100MΩMIN
适合电线 Applicable Wire**	8mm2Max
极数 Number of poles	3Poles

TYPE:IN60BK-C	Ratings
Dimensions(mm) 	定格绝缘电压 Rated Insulation Voltage
	600V
定格绝缘电流 Rated Insulation Current	90A
	耐电压 Support Voltage
绝缘抵抗 Insulation Resistance	100MΩMIN
适合电线 Applicable Wire**	22mm2Max
极数 Number of poles	1Poles

TYPE:IN200K-C	Ratings
Dimensions(mm) 	定格绝缘电压 Rated Insulation Voltage
	600V
定格绝缘电流 Rated Insulation Current	240A
	耐电压 Support Voltage
绝缘抵抗 Insulation Resistance	100MΩMIN
适合电线 Applicable Wire**	100mm2Max
极数 Number of poles	1Poles